

Ph.: +39 (011) 4701510 or 4701511 or 4704541 Fax +39 (011) 4703910 - Email: info@reinol.it

TECHNICAL DATA SHEET

SOLPERM INKS - Top Quality

TECHNICAL CHARACTERISTICS

Top quality solvent-based permanent marker inks. They are dye-based formulated for filter system markers. They are characterized by a very good lightfastness.

Suitable for any non-porous surface but also for paper or cardboards.

Colour ref. No:	BLACK 286	BLUE 3071	RED 3255
Viscosity, cps (25 °C) Brookfield Small Sample Adapter Spindle SC4-18, rpm 200 (cps, 25°C)	< 15	< 15	< 15
pH:	7±1	3,5 ± 1	7±1
Light Fastness	High	High	High

SUITABLE COMPONENTS

Markers should ideally be stored horizontally and should be capped

Nibs/Tips: Polyester for alcohol-based inks, porosity 55-60%

Reservoir: Polyester, density 0,170-0,190 g/cm3

Body: Polypropylene, Polyethylene

Cap, Front Section: Polypropylene, Polyethylene

It is recommended to thoroughly test the components selected.

HANDLING INSTRUCTIONS

Store between 15°C and 30°C. Do not expose loose ink to

temperatures higher than 30°C. Protect from frost and avoid direct sunlight. Storage temperatures above 30°C can result in reduced shelf life of the inks.

CAUTION: the inks are flammable liquids! Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. After use clean the filling unit with alcohol or MEK. Drums should be closed tightly during storage.

PACKING

50 KG net Plastic or Metal Drums 200 KG net Plastic or Metal Drums